

# DECLARATION OF PERFORMANCE



**N° 870522056-2**

**1. NAME AND IDENTIFICATION CODE**

**PRODUCT:** Compact High Pressure Decorative Laminates (HPL) – Thick Lam for indoor and outdoor application. Thickness between 6 y 20 mm.

**2. MANUFACTURER NAME AND ADDRESS**

Lamitech S.A.S.

Zona Industrial de Mamonal Km 13, Cartagena - Colombia

**3. APPLICATION**

Indoor and outdoor application walls or ceilings subject to reaction to fire regulation

**4. PERFORMANCE EVALUATION AND VERIFYING SYSTEM.**

System 1

**5. NOTIFIED ORGANIZATION.**

**NAME:** TECNALIA R&I CERTIFICACION, S.L.

**ASSIGNMENT:** Evaluation of the constancy of performance

**EVALUATION SYSTEM:** 1

**DOCUMENT AND DATE OF ISSUE:** Product performance certificate of completion  
# 054607-2. November 24/2015

## 6. DECLARED PERFORMANCE

Característica esenciales	Prestaciones	Especificaciones Técnicas armonizadas
Reacción al fuego / reaction to fire / brandverhalten	Euroclase B-s2, d0	<b>EN438 – 7: 2005</b>
Resistencia al fuego/Fire Resistance / feuerwiderstand	NDP	
Permeabilidad al vapor de agua/wáter vapour resistance / Wasserdampfdurchlässigkeit	NDP	
Resistencia a las fijaciones / resistance to fixings / Verankerungsfestigkeit	6-8 mm: 2000 N 8-10 mm: 3000 N 10-20 mm: 4000 N	
Aislamiento acústico al ruido aéreo/ direct airborne sound insulation/direkte luftschalldämmung	NPD	
Resistencia de tracción en flexión/flexural strength / Biegefestigkeit	PASA / PASS / BESTANDEN	
Resistencia /Conductividad térmica	NDP	
Contenido en pentaclorofenol/pentachlorophenol content /Pentachlorophenol - Gehalt	NDP	
Emisión de formaldehído/release of formaldehyde/ formaldehydabgabe	E1	
Absorción acústica/sound absorotion/schallabsorption	NDP	
Resistencia al choque térmico/termal shock resistance /temperaturwechselbeständigkeit	PASA / PASS / BESTANDEN	
Densidad/density/dichte	1350 kg/m <sup>3</sup>	
Resistencia a la Humedad/durability resistance to wet conditions / dauerhaftigkeit – bestandigkeit gegen feuchte	PASA / PASS / BESTANDEN.	
Resistencia al agua hirviendo/durability to immersion in boiling wáter / dauerhaftigkeit – bestandigkeit gegenuber eintauchen in siedendes wasser	PASA / PASS / BESTANDEN	

**7. PRODUCT CE LABELING AND DOCUMENTS** : the product will use a small CE label just as well as dispatch documents

Declared performances in point 1 comply with those in point 6

This declaration of performance is issued under sole responsibility of the manufacturer identified in point 2

Signed for and on behalf of the manufacturer LAMITECH S.A.S



---

Ivan Arias Camacho  
Technical Manager Lamitech S.A.S.

Cartagena – Colombia, November 27 / 2015